



VANCOUVER PLAYHOUSE

| # | Dis | Type | DIM | Purpose | Channel |
|---|------------|--------------|-----------|--------------|-------------------|
| PIT PIPE (2'6" from DSC) trim 21' 26 weights total | | | | | |
| 1 | 20' | 26 ° | 11 | - DSC fronts | 72 L200 |
| 2 | 18' | 36 ° | 12A | sl high side | 33 R3204 |
| 3 | 10' | VL 1K | 39 | 2/305 | 422 pwr 62 |
| 4 | 7'6" | 36 ° | 14A | cs high side | 32 R3204 |
| 5 | 3'6" | 36 ° | 12B | sl high side | 33 R3204 |
| 6 | 1' | 36 ° | 13A | special top | 314 R3204 |
| 7 | C | | 57 | spare | R3204 |
| 8 | 1' | 36 ° | 13B | special top | 314 R3204 |
| 9 | 3'6" | 36 ° | 15A | sr high side | 31 R3204 |
| 10 | 7'6" | 36 ° | 14B | cs high side | 32 R3204 |
| 11 | 10' | VL 1K | 44 | 2/440 | 421 pwr 62 |
| 12 | 18' | 36 ° | 15B | sr high side | 31 R3204 |
| 13 | 20' | 26 ° | 16 | - DSC fronts | 71 L200 |

Main Drape (w/ fullness) 0/0 DSC line (center of proscenium centerline)

| # | Dis | Type | DIM | Purpose | Channel |
|--|------------|--------------|------------|--------------------------|--------------------|
| 1st LX (lineset 2, 5' from DSC – note that this is center of prosc) trim 22' | | | | | |
| 1 | 26' | 26° | 170 | special | 328 |
| 2 | 22' | 36 ° | 168 | high side | 38 R3208 |
| 3 | 21' | 36 ° | 167 | - Scroll Tip (2/10) | 74 |
| 4 | 20' | 50° | 166 | - gobo | 82 |
| 5 | 17' | 36° | 165 | US fronts | 54 L200 |
| 6 | 15' | 36 ° | 163 | high side | 37 R3208 |
| | 13' | Work | 382 | | |
| 7 | 12' | 36° | 161 | special/ Gobo | 317 |
| 8 | 10' | VL 1K | 160 | - Special (2/251) | 424 pwr 159 |
| 9 | 8' | 36 ° | 158 | high side | 36 R3208 |
| 10 | 6' | 36° | 156 | high side | 38 R3208 |
| 11 | 5' | 36 ° Lustr2 | 155 | LED special | 373 R3208 |
| | 4' | Work | 382 | | |
| 12 | 1'6" | 36 ° | 153 | - high side | 35 R3208 |
| 13 | C | 36 ° Lustr2 | 151 | LED special | 372 |
| 14 | 1'6" | 36 ° | 150 | - high side | 37 R3208 |
| | 4' | Work | 382 | | |
| 15 | 5' | 36° Lustr2 | 148 | LED special | 371 |
| | R3208 | | | | |
| 16 | 6' | 36° | 147 | high side | 34 R3208 |
| 17 | 8' | 36° | 146 | high side | 36 R3208 |
| 18 | 10' | VL 1K | 145 | - Special (2/413) | 423 pwr 144 |
| 19 | 12' | 36° | 141 | special/Gobo | 315 |
| | 13' | Work | 382 | | |
| 20 | 14' | 26° | 140 | lec back | 331 |
| 21 | 15' | 36° | 139 | high sides | 35 R3208 |
| 22 | 17' | 36 ° | 136 | US fronts | 53 G848 |
| 23 | 20' | 36° | 135 | - Gobo | 81 |
| 24 | 21' | 36° | 134 | - Scroller Tip (2/7) | 73 |
| 25 | 22' | 36 ° | 132 | high side | 34 R3208 |
| 26 | 26' | 26° | 131 | special | 327 |

Border (lineset 6) trim 18' 6" 7'8" from DSC
 Leg (lineset 7) note pipe sits at 22' 8'2" from DSC

| # | Dis | Type | Dim | Purpose | Channel |
|---|-----|------|-----|---------|---------|
|---|-----|------|-----|---------|---------|

2LX (lineset 9) trim 22' 9'6" from DSC

| | | | | | | |
|----------|------------|--------------|------------|---|---------------------|------------|
| 1 | 21' | 36° | 171 | - | Scroller Tip (2/2) | 76 |
| 2 | 20' | 50° | 172 | - | gobo tip | 84 |
| 3 | 12' | 36° | 173 | | special | 320 |
| 4 | 10' | VL1K | 174 | | (2/332) | 426 |
| 5 | 6' | 36° Lustr2 | 175 | | LED sp (2/ | 376 |
| 6 | 1' | 36° Lustr2 | 179 | | LED special | 375 |
| 7 | 1' | VL1K | | | (2/428) | 427 |
| 8 | 8' | 36° | 182 | - | LED sp (2/ | 374 |
| 9 | 10' | VL 1K | 181 | | (2/359) | 425 |
| 10 | 12' | 36° | 180 | | special | 318 |
| 11 | 20' | 36° | 178 | - | gobo tip | 83 |
| 12 | 21' | 36° | 177 | - | Scroller Tip (2/12) | 75 |

OLEO (black traveller with fullness) (lineset 11) 10'8" from DSC

3LX Par Pipe (lineset 14) trim 22'6" 12'2" from DSC

| | | | | | | | |
|----|-------|---------|-----|---|------|-----|-------|
| 1 | 15'8" | Par | 206 | - | warm | 141 | O/W |
| 2 | 14'6" | Par | 205 | | cc | 161 | R3204 |
| 3 | 13'4" | Par | 204 | | warm | 142 | |
| 4 | 12'2" | Par | 203 | - | cc | 162 | |
| 5 | 11' | Par med | 202 | | warm | 143 | |
| 6 | 9'10" | Par med | 201 | | cc | 163 | |
| 7 | 7'10" | Par | 200 | - | warm | 101 | R26 |
| 8 | 6'8" | Par | 199 | | cool | 121 | R80 |
| 9 | 5'6" | Par | 198 | | warm | 102 | |
| 10 | 4'4" | Par | 197 | - | cc | 122 | |
| 11 | 3'2" | Par | 196 | | warm | 103 | |
| 12 | 2' | Par | 195 | | cool | 123 | |
| 13 | 2' | Par | 194 | - | warm | 104 | |
| 14 | 3'2" | Par | 193 | | cool | 124 | |
| 15 | 4'4" | Par | 192 | | warm | 105 | |
| 16 | 5'6" | Par | 191 | - | cool | 125 | |
| 17 | 6'8" | Par | 190 | | warm | 106 | |
| 18 | 7'10" | Par | 189 | | cool | 126 | |
| 19 | 9'10" | Par med | 188 | - | warm | 151 | O/W |
| 20 | 11' | Par med | 187 | | cc | 171 | R3204 |
| 21 | 12'2" | Par | 186 | | warm | 152 | |
| 22 | 13'4" | Par | 185 | - | cc | 172 | |
| 23 | 14'6" | Par | 184 | | warm | 153 | |
| 24 | 15'8" | Par | 183 | | cc | 173 | |

Border (lineset 17) trim 18' 6" 13'8" from DSC
 Leg (lineset 18) note pipe sits at 22' height 14'2" from DSC

4LX (lineset 20) trim 22' 15'6" from DSC

| | | | | | | |
|---|-----|-----|-----|---|--------------|-----|
| 1 | 21' | 36° | 213 | - | tip special | 78 |
| 2 | 20' | 50° | 214 | - | gobo | 86 |
| 3 | 12' | 36° | 215 | - | special/gobo | 323 |
| 4 | C | 36° | 216 | | special | 322 |
| 5 | 12' | 36° | 217 | - | special | 321 |
| 6 | 20' | 36° | 218 | - | gobo | 85 |
| 7 | 21' | 36° | 207 | - | tip special | 77 |

Spare circuits: 29

Black Traveler (lineset 22) 16'8" from DSC

Dis Type Dim Purpose Channel

5LX (lineset 25) trim 22'6" 18'6" from DSC

| | | | | | | | |
|----|-------|-----|-----|---|------|-----|-------|
| 1 | 15'8" | Par | 224 | - | warm | 144 | O/W |
| 2 | 14'6" | Par | 223 | | cc | 164 | R3204 |
| 3 | 13'4" | Par | 222 | | warm | 145 | |
| 4 | 12'2" | Par | 221 | - | cc | 165 | |
| 5 | 11' | Par | 220 | | warm | 146 | |
| 6 | 9'10" | Par | 219 | | cc | 166 | |
| 7 | 7'10" | Par | 230 | - | o/w | 107 | |
| 8 | 6'8" | Par | 229 | | cool | 127 | |
| 9 | 5'6" | Par | 228 | | warm | 108 | |
| 10 | 4'4" | Par | 227 | - | cc | 128 | |
| 11 | 3'2" | Par | 226 | | o/w | 109 | R26 |
| 12 | 2' | Par | 225 | | cool | 129 | R80 |
| 13 | 2' | Par | 236 | - | o/w | 110 | |
| 14 | 3'2" | Par | 235 | | cool | 130 | |
| 15 | 4'4" | Par | 234 | | o/w | 111 | |
| 16 | 5'6" | Par | 233 | - | cool | 131 | |
| 17 | 6'8" | Par | 232 | | o/w | 112 | |
| 18 | 7'10" | Par | 231 | | cool | 132 | |
| 19 | 9'10" | Par | 242 | - | warm | 154 | O/W |
| 20 | 11' | Par | 241 | | cc | 174 | R3204 |
| 21 | 12'2" | Par | 240 | | warm | 155 | |
| 22 | 13'4" | Par | 239 | - | cc | 175 | |
| 23 | 14'6" | Par | 238 | | warm | 156 | |
| 24 | 15'8" | Par | 237 | | cc | 176 | |

Border (lineset 28) trim 18'6" 19'8" from DSC

Leg (lineset 29) note pipe sits at 22' height 20' 2" from DSC

| # | Dis | Type | Dim | Purpose | Channel |
|------------|--------------|-------------|------------|----------------|------------|
| 6LX | (lineset 32) | | trim 22'6" | 22' from DSC | |
| 1 | 20' 6" | 36° | 243 | tip | 80 |
| 2 | 19' 6" | 50° | 244 | - gobo | 88 |
| 3 | 15'8" | Par | 260 | - warm | 147 |
| 4 | 14'6" | Par | 259 | cc | 167 |
| 5 | 13'4" | Par | 258 | o/w | 148 |
| 6 | 12'2" | Par | 257 | - cool | 168 |
| 7 | 11' | Par med | 256 | warm | 149 |
| 8 | 9'10" | Par med | 255 | cc | 169 |
| 9 | 10" | 36° | 245 | - special/gobo | 326 |
| 10 | 7'10" | Par | 266 | - o/w | 113 |
| 11 | 6'8" | Par | 265 | cool | 133 |
| 12 | 5'6" | Par | 264 | o/w | 114 |
| 13 | 4'4" | Par | 263 | - cool | 134 |
| 14 | 3'2" | Par | 262 | o/w | 115 |
| 15 | 2' | Par | 261 | cool | 135 |
| 16 | C | VL1K | 246 | 2/278 | 428 |
| 17 | 2' | Par | 272 | - o/w | 116 |
| 18 | 3'2" | Par | 271 | cool | 136 |
| 19 | 4'4" | Par | 270 | o/w | 117 |
| 20 | 5'6" | Par | 269 | - cool | 137 |
| 21 | 6'8" | Par | 268 | o/w | 118 |
| 22 | 7'10" | Par | 267 | cool | 138 |
| 23 | 10" | 36° | 247 | - special/gobo | 324 |
| 24 | 9'10" | Par med | 278 | - warm | 157 |
| 25 | 11' | Par med | 277 | cc | 177 |
| 26 | 12'2" | Par | 274 | warm | 158 |
| 27 | 13'4" | Par | 273 | - cc | 178 |
| 28 | 14'6" | Par | 276 | warm | 159 |
| 29 | 15'8" | Par | 275 | cc | 179 |
| 30 | 19' 6" | 50° | 248 | tip | 79 |
| 31 | 20' 6" | 36° | 249 | - gobo | 87 |

Border (lineset 36) trim 18' 6" 25'3" from DSC

Leg (lineset 37) note pipe sits at 22' height 25' 9" from DSC

8 LX (lineset 42) CYC trim 24' 32' from DSC

| | | | | | |
|----|----------|-----|--------|-----|-------|
| 1 | 1k cell | 279 | Ctb | 195 | R3204 |
| 2 | 1k cell | 282 | Blue | 187 | R80 |
| 3 | 1k cell | 285 | Indigo | 183 | R379 |
| 4 | 1 k cell | 288 | Bluish | 191 | R3220 |
| 5 | 1k cell | 279 | Ctb | 195 | |
| 6 | 1k cell | 282 | Blue | 187 | |
| 7 | 1k cell | 285 | Red | 183 | |
| 8 | 1k cell | 288 | Green | 191 | |
| 9 | 1k cell | 280 | Ctb | 194 | |
| 10 | 1k cell | 283 | Blue | 186 | |
| 11 | 1k cell | 286 | Red | 182 | |
| 12 | 1k cell | 289 | Green | 190 | |
| 13 | 1k cell | 280 | Ctb | 194 | |
| 14 | 1k cell | 283 | Blue | 186 | |
| 15 | 1k cell | 286 | Red | 182 | |
| 16 | 1k cell | 289 | Green | 190 | |
| 17 | 1k cell | 281 | Ctb | 193 | |
| 18 | 1k cell | 284 | Blue | 185 | |
| 19 | 1k cell | 287 | Red | 181 | |
| 20 | 1k cell | 290 | Green | 189 | |
| 21 | 1k cell | 281 | Ctb | 193 | R3204 |
| 22 | 1k cell | 284 | Blue | 185 | R80 |
| 23 | 1k cell | 287 | Indigo | 181 | R379 |
| 24 | 1k cell | 290 | Bluish | 189 | R3220 |

Black Backdrop (lineset 43) 32'8" from DSC

| | | | | | | |
|--------------------|--------|----------|----|-----------------------------|-----|-------|
| City Hall (#1 FOH) | | | | data pwr 68 | | |
| 1) | 20' | 26 ° | 65 | caliper special | 313 | R3208 |
| 2) | 18' | 26° iris | 63 | - special | 312 | |
| 3) | 15' | 26° iris | 61 | special | 311 | |
| 4) | 12' | 26° | 58 | special | 310 | |
| 5) | 9' 6" | 19 ° | 55 | i-cue left/ iris (2/50/31) | 403 | |
| 6) | 7' | 26° iris | 54 | special | 309 | |
| 7) | 4' | 26 ° | 53 | special | 308 | |
| 8) | 6" L | 19 ° | 51 | icue centre/ iris (2/45/32) | 402 | |
| 9) | 6" R | 26 ° | 50 | special | 307 | |
| 10) | 4' | 26 ° | 47 | special | 306 | |
| 11) | 7' | 26° iris | 46 | special | 305 | |
| 12) | 9' 6" | 19° | 45 | i-cue right/iris (2/80/33) | 401 | |
| 13) | 12' | 26° | 41 | special | 304 | |
| 14) | 15' 6" | 26° iris | 40 | special | 303 | |
| 15) | 18' | 26° iris | 38 | - special | 302 | |
| 16) | 20' | 26 ° | 34 | caliper special | 301 | R3208 |

SL Slot Room (36' from DSC)

| | | | | | | |
|--------|------|-----|-----|--------------|-----|------|
| 1) 26° | 750w | 115 | top | Gobo tip | 50 | |
| 2) 26° | 750w | 116 | | ldr ext W | 48 | R54 |
| 3) 26° | 750w | 117 | | ldr ext C | 46 | G848 |
| 4) 26° | 750w | 118 | | ldr ext gobo | 44 | |
| 5) 26° | 575w | 66 | | panel | 282 | |

Note slot boom on caliper from 0" to 12' directly below slot room

| | | | | | | |
|-----|------|-----|--|---------------|----|--|
| 36° | 750w | 102 | | pit head high | 42 | |
|-----|------|-----|--|---------------|----|--|

SR Slot Room

| | | | | | | |
|--------|------|-----|-----|--------------|-----|------|
| 1) 26° | 750w | 119 | top | Gobo tip | 49 | |
| 2) 26° | 750w | 120 | | ldr ext W | 47 | R54 |
| 3) 26° | 750w | 121 | | ldr ext C | 45 | G848 |
| 4) 26° | 750w | 122 | | ldr ext Gobo | 43 | |
| 5) 26° | 575w | 33 | | panel | 282 | |

Note slot boom on caliper from 0" to 12' directly below slot room

| | | | | | | |
|-----|------|-----|--|---------------|----|--|
| 36° | 750w | 114 | | pit head high | 41 | |
|-----|------|-----|--|---------------|----|--|

Box Boom Left (38' from DSC)

| | | | | | | |
|--------|------|----|--|--------------|----|-------|
| 1) 26° | 750w | 92 | | far pit hs | 11 | R3208 |
| 2) 26° | 750w | 91 | | mid pit hs | 12 | R3208 |
| 3) | | 93 | | next to wall | | |
| 4) 26° | 750w | 95 | | far | 14 | R333 |
| 5) 26° | 750w | 94 | | mid | 13 | R333 |
| 6) 26° | | 98 | | | | |
| 7) | | 97 | | far | 15 | |
| 8) | | 96 | | mid | 16 | |

Box Boom Right

| | | | | | | |
|--------|--|-----|--|---------------|----|-------|
| 1) 26° | | 103 | | pit high side | 11 | R3208 |
| 2) 26° | | 104 | | pit high side | 12 | R3208 |
| 3) | | 105 | | next to wall | | |
| 4) 26° | | 106 | | far | 13 | R333 |
| 5) 26° | | 107 | | mid | 14 | R333 |
| 6) 26° | | 108 | | | | |
| 7) | | 109 | | far | 15 | |
| 8) | | 110 | | mid | 16 | |

#2 FOH (31' from DSC)

| | | | | | | |
|-----|-----|-----|-----|----|---|-------|
| 1) | 22' | 19° | 750 | 32 | 3 | R3208 |
| 2) | | | | | | |
| 3) | | | | | | |
| 4) | 10' | 19° | 750 | 28 | 2 | R3208 |
| 5) | | | | | | |
| 6) | 6' | 19° | 750 | 26 | 3 | R3208 |
| 7) | 6' | 19° | 750 | 24 | 1 | R3208 |
| 8) | | | | | | |
| 9) | 10' | 19° | 750 | 22 | 2 | R3208 |
| 12) | 22' | 19° | 750 | 18 | 1 | R3208 |

#3 FOH (48' from DSC)

| | | | | | |
|-----|-----|-----|----|------|-------|
| 1) | 20' | 19° | 29 | 23 | |
| 2) | 16' | 14° | 10 | 8 | R3208 |
| 3) | 10' | 19° | 9 | 22 C | |
| 4) | 8' | 14° | 3 | 7 | R3208 |
| 5) | 6' | 19° | 2 | 6 | R3208 |
| 6) | 5' | 19° | 29 | 23 | |
| 7) | 5' | 19° | 4 | 21 | MC |
| 8) | 6' | 19° | 5 | 5 | R3208 |
| 9) | 7' | 19° | 1 | | spare |
| 10) | 8' | 19° | 6 | | spare |
| 11) | 10' | 19° | 9 | 22 C | R3208 |
| 12) | 16' | 14° | 7 | 4 | R3208 |
| 13) | 20' | 19° | 4 | 21 | MC |

Prosc perch Left

1 44" ds of prosc / 11' height 36° Lustr2 93 291

Smoke Pocket Left

1 12" us of CC (height of ladders) 36° Lustr2 far 293
 2 36° Lustr2 near 292

SL Ladder (four sections – track up and down stage) (30' from CS)

| | | | | | | |
|---|------|-----|-----|---|---------------|-----|
| 1 | C@3' | 26° | 291 | - | Gobo far | 281 |
| 2 | | 36° | 292 | | spare circuit | |
| 3 | | 36° | 293 | | spare circuit | |
| 4 | | 36° | 294 | | Gobo near | 282 |
| 1 | | 26° | 295 | - | Gobo far | 283 |
| 2 | | 26° | 296 | | Lustr2 far | 295 |
| 3 | | 36° | 296 | | Lustr2 near | 294 |
| 3 | | 36° | 297 | | spare circuit | |
| 4 | | 36° | 298 | | Gobo near | 284 |
| 1 | | 26° | 299 | - | Gobo far | 285 |
| 2 | | 26° | 300 | | Lustr2 far | 297 |
| 3 | | 36° | 300 | | Lustr2 near | 296 |
| 3 | | 36° | 301 | | spare circuit | |
| 4 | | 36° | 302 | | Gobo near | 286 |
| 1 | C@3' | 26° | 303 | - | Gobo far | 287 |
| 2 | | 36° | 304 | | spare circuit | |
| 3 | | 36° | 305 | | spare circuit | |
| 4 | | 36° | 306 | | Gobo near | 288 |

Prosc perch Right

| | | | | | |
|---|------------------------------|------------|-----|--|-----|
| 1 | 44" ds of prosc / 11' height | 36° Lustr2 | 101 | | 271 |
|---|------------------------------|------------|-----|--|-----|

Smoke Pocket Right

| | | | | | |
|---|--------------|---------------------|------------|------|-----|
| 1 | 12" us of CC | (height of ladders) | 36° Lustr2 | far | 273 |
| 2 | | | 36° Lustr2 | near | 272 |

SR Ladder (four sections – track up and down stage)

| | | | | | | |
|---|------|-----|-----|---|---------------|-----|
| 1 | C@3' | 26° | 307 | - | Gobo far | 261 |
| 2 | | 36° | 308 | | spare circuit | |
| 3 | | 36° | 309 | | spare circuit | |
| 4 | | 36° | 310 | | Gobo near | 262 |
| 1 | | 26° | 295 | - | Gobo far | 263 |
| 2 | | 26° | 296 | | Lustr2 far | 275 |
| 3 | | 36° | 296 | | Lustr2 near | 274 |
| 3 | | 36° | 297 | | spare circuit | |
| 4 | | 36° | 298 | | Gobo near | 264 |
| 1 | | 26° | 295 | - | Gobo far | 265 |
| 2 | | 26° | 296 | | Lustr2 far | 277 |
| 3 | | 36° | 296 | | Lustr2 near | 276 |
| 3 | | 36° | 297 | | spare circuit | |
| 4 | | 36° | 298 | | Gobo near | 266 |
| 1 | | 26° | 319 | - | Gobo far | 267 |
| 2 | | 36° | 320 | | spare circuit | |
| 3 | | 36° | 321 | | spare circuit | |
| 4 | | 36° | 322 | | Gobo near | 268 |

Balcony Rail (45' from DSC)

| | | | | | | |
|---|--|-----|----|--|----------------|-----|
| 1 | | 50° | 90 | | curtain warmer | 281 |
| 2 | | 10° | 87 | | | 284 |
| 3 | | 10° | 84 | | VRS gobo | 283 |
| 4 | | 10° | 80 | | | 282 |
| 5 | | 50° | 73 | | curtain warmer | 281 |

Caliper BOOM LEFT

| | | | | |
|---|------|-----|-----|-----|
| 1 | 5' | 36° | 99 | 252 |
| 2 | 2'6" | 36° | 100 | 242 |
| 3 | 1' | 36° | 101 | 232 |

Caliper BOOM RIGHT

| | | | | |
|---|------|-----|-----|-----|
| 1 | 5' | 36° | 111 | 245 |
| 2 | 2'6" | 36° | 112 | 241 |
| 3 | 1' | 36° | 113 | 231 |

COUNT:

Total lighting equipment inventory (includes hanging fixtures and spare barrels)

Ellipsoidal

| | | | | |
|---------------------|----------|-----|------|--------------------------------------|
| ETC Source four 10° | 3 total | HPL | .75k | |
| ETC Source four 14° | 4 total | HPL | .75k | |
| ETC Source four 19° | 29 total | HPL | .75k | |
| ETC Source four 26° | 55 total | HPL | .75k | |
| ETC Source four 36° | 51 total | HPL | .75k | additional source four are available |
| ETC Source four 50° | 22 total | HPL | .75k | from QET stock next door |

Spare barrels: 36° - 21 (there are 164 lights and 185 barrels)

All numbers include lights hung as per instrument schedule.

| | |
|--------------------------------|----|
| ETC source four LUSTR2 LED 26° | 6 |
| ETC source four LUSTR2 LED 36° | 14 |

| | | | | |
|--------------------------|----|-----|--------|--------------------|
| Par 64 Rack o' six | 12 | FFS | 1k | CP95 or EXG (wide) |
| Par 64 | 25 | FFR | 1k | CP62 (med) |
| Fresnel | | | | |
| Castor 270 - 12.5" | 20 | | 2k | Only 3 Barn Doors! |
| Strand 3380 - 6" | 46 | | BTR 1k | w. Barn Doors |
| Rank Mizar MK.2 - 3" | 10 | FEV | .3k | No Barn doors |
| Cyc Cell | | | | |
| Iris lanaro Sky Cyc | | | | |
| two cell units | 12 | FFT | 1k | |
| lanaro Pallas Ground row | | | | |
| four cell units | 11 | FHM | 1k | |

Other Conventional:

| | | | | |
|------------------------|----|-----|-----------|-----------|
| Mini strips | | | | |
| (3 cir/30 bulb) 4 | | EYC | 75w | (med) |
| MR-16 spots | 30 | | 75w | (Various) |
| Century Beam Projector | | | | |
| 12" | 6 | BTP | .75k | |
| Kliegal Scoop 15" | 12 | | Mogul .3k | |
| Moving: | | | | |
| VL 1000 ts | 6 | | | 1k |
| Data flash | 2 | | | |
| Atomic 3k strobe | 1 | | | 110 volt |

Accessories

| | | |
|---------------------|---|------------------------|
| Rosco i-Que mirrors | 8 | |
| 4 pin power supply | 6 | |
| DMX opto splitter | | 2 |
| gobo rotators | | 6 |
| scrollers | | 12 'christie B scroll' |

| | | |
|-------------------|----|---|
| Dmx iris | | 8 |
| Drop in iris | | 8 |
| Barn door – 12.5" | | 3 |
| Barn door – 6" | 50 | |

House dimmer circuits are L5-20 (120v 20amp)
5k Dimmers use "joy" 3 pin connector